	and the second second
CLASSIER	CNO CONTROL SERVICE &
3210311	EUSPIUP BITAL
CENTRAL	CICONFIDENTIAL INTELLIGENCE AGENCY

INFORMATION FROM FOREIGN DOCUMENTS OR RADIO BROADCASTS

REPORT CD NO.

50X1-HUM

COUNTRY

North Korea

DATE OF

SUBJECT

Communications

INFORMATION

1949

HOW

Monthly periodical

DATE DIST.

WHERE

PUBLISHED

PUBLISHED

Pyongyang

DATE **PUBLISHED** 5 Mar 1949

NO. OF PAGES

SULLEMENT TO

LANGUAGE

Korean

REPORT NO.

THIS IS UNEVALUATED INFORMATION

SOURCE

Minju Chesin.

TRIECOMMUNICATIONS SYSTEM IN NORTH KORRA

North Krea's telecommunications system is satisfactory in terms of quantity, but it is poor in quality. The current situation of the telephone and telegraph facilities of North Korea is summarized below.

Materials and Equipme t

There have been some shortcomings found both in the supply and in the use of materials and equipment. In obtaining materials, whether through purchase or denation, no careful inspection is made to determine whether they meet the spequfications with regard to the quality, size, workability, and the use to which materials are put. Sc far, there are no written specifications prescribing standards for all materials.

Judging from past records, the degeneration of the telecommunications facilities in terms of quality was due largely to the poor selection and utilization of materials. The importance of using the right materials in the right place has been generally overlooked.

Planning and Method of Englisering

Short-sighted planning in the network layout, including surveying, selecting of route, location, setting up posts, etc., has been one of the serious draw-backs. To cite specific examples, overhead wires have been installed without due regard to what is required both now and in the future. Consequently, unnecessary waste occurs later when circuits are installed and changes are required in the original layout. Improper installation, which causes faster breakdown of the metwork, has been found in the main lines as well as in branch lines. In areas where natural bazards, such as heavy snow and storms are frequent, the wires installed are of improper size and they cannot withstand hazards. Distances between posts are too far for such areas without reinforcement of some kind.

CLASSIFICATION CAMEDOMY

CENCEL ICHTION CONTRACTOR STREET				
STATE	NAVY	X	NSRB	DISTRIBUTION
ARMY	AIR	X	FBI	والمراج والمامي والمبطوع والسبوا والمبارا

Sanitized Copy Approved for Release 2011/07/18: CIA-RDP80-00809A000600230921-4

CONFIRMINAL

50X1-HUM

Wiring is done inefficiently in both straight and curved line formations, such as laying the wires counter to the terrain, uneverness of distances between posts, uneverness of the heights of posts, etc.

The entire situation, however, seems to point to the lack of technical knowledge on the part of technicians along with the shortage of skilled workers in this field. Since this has been the basic problem, efforts on the part of the central and local authorities concerned are being strongly demanded for improvement in the supply of capable technicians.

- E N D -

POR INCHINAL